# NanoPack™ CTS SEALED SERIES AND



NanoPack™ CTS 8W Female

### **AVAILABLE CONFIGURATIONS**

Cavity Count (ways)	8, 12*
Cavity Configurations (mm)	0.5
Cable range (mm²)	0.13 - 0.35
Genders	Female
ТРА Туре	Pre-assembled ASL**
CPA	Optional
Sealing Type	Multi wire mat seal
Centerline Spacing (mm)	1.8
Specification	VW75174-LV214; IEC68; DIN: IEC60512; EN60068

<sup>\*</sup> Other cavities available, please consult us

<sup>\*\*</sup> ASL - Active Secondary lock



### **APPLICATIONS**

Mid and short range radars, Cameras, Tire pressure sensors exposed to humidity and liquid splashes

### **BENEFITS**


- Connector Position Assurance (CPA) is optional for 8W version. Optimized space saving version without CPA, bottom or top locking latch possible
- Housings & terminals are designed as per VDA/AK guidelines

### **FEATURES**

- Designed for high temperatures and vibration profiles
- Aptiv is responsible for the sealed 0.5 footprint at VDA/AK
- Ergonomic handling and touching surface as per manual mating guideline (USCAR)

## TECHNICAL CHARACTERISTICS

Mating force	75 N
Contact pull out force	≥ 25 N primary ≥ 35 N secondary
Contact insertion force	~ 2 N
Automated terminal insertion	Capable & compatible



\* Peak temperature: 130°C

See back page for representative part numbers and packaging dimensions.

# **About Aptiv**

Aptiv is a global technology company that develops safer, greener and more connected solutions enabling the future of mobility.

Visit aptiv.com




Cavity count	Blade size (mm)	Gender	AK footprint	Dimensions W x H x L (mm)	Part number	Index	Color
8	0.5	F	Yes	16.7 x 17.5 x 29.85	35364118	Α	Black
8	0.5	F	Yes	16.7 x 17.5 x 29.85	35371049	В	Black
8	0.5	F	Yes	16.7 x 17.5 x 29.85	35371050	С	Black
8	0.5	F	No	16.25 x 13.15 x 26.35	35355142	Α	Black
8	0.5	F	No	16.25 x 13.15 x 26.35	35355143	В	Black
8	0.5	F	No	16.25 x 13.15 x 26.35	35355144	С	Black
12	0.5	F	Yes	20.3 x 17.5 x 29.85	35511141	Α	Black

# REQUIRED ACCESSORIES

Туре	Color	Angle	Part number
Cover	Black	180°	Consult us
Cover	Black	90° right	Consult us
Cover	Black	90° left	Consult us

# DIMENSION MEASUREMENT SAMPLE





# COMPATIBLE WITH



Part numbers, specifications, dimensions and performance data in this document are for general references only and are subject to change without notice. To verify product information, please contact an Aptiv representative.

